




BEARING CORP. LTD.



45 mm x 75 mm x 16 mm SKF 7009
ACD/HCP4A angular contact ball bearings

Bearing No. 7009 ACD/HCP4A

7009 ACD/HCP4A Bearing 2D drawings and 3D CAD models

Size	75x45x16 mm
Bore Diameter	75 mm
Outer Diameter	45 mm
Width	16 mm
d	45 mm
D	75 mm
B	16 mm
d ₁	54.2 mm
d ₂	54.2 mm
D ₁	65.8 mm
r _{1,2} - min.	1 mm
r _{3,4} - min.	0.3 mm
a	22.1 mm
d _a - min.	49.6 mm
d _b - min.	49.6 mm
D _a - max.	70.4 mm
D _b - max.	73 mm
r _a - max.	1 mm
r _b - max.	0.3 mm
d _n	56.2 mm
Basic dynamic load rating - C	27.6 kN
Basic static load rating - C ₀	21.6 kN
Fatigue load limit - P _u	0.9 kN
Limiting speed for grease	20000 r/min



BEARING CORP. LTD.

Lubrication	
Limiting speed for oil lubrication	32000 mm/min
Ball - D_w	9.525 mm
Ball - z	17
G_{ref}	3.3 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	170 N
Preload class B - G_B	340 N
Preload class C - G_C	680 N
Preload class D - G_D	1360 N
Calculation factor - f	1.09
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.05
Calculation factor - f_{2D}	1.08
Calculation factor - f_{HC}	1.02
Preload class A	146 N/micron
Preload class B	192 N/micron
Preload class C	254 N/micron
Preload class D	343 N/micron



BEARING CORP. LTD.

d_1	54.2 mm
d_2	54.2 mm
D_1	65.8 mm
$r_{1,2}$ min.	1 mm
$r_{3,4}$ min.	0.3 mm
d_a min.	49.6 mm
d_b min.	49.6 mm
D_a max.	70.4 mm
D_b max.	73 mm
r_a max.	1 mm
r_b max.	0.3 mm
d_n	56.2 mm
Basic dynamic load rating C	27.6 kN
Basic static load rating C_0	21.6 kN
Fatigue load limit P_u	0.9 kN
Attainable speed for grease lubrication	20000 r/min
Attainable speed for oil-air lubrication	32000 r/min
Ball diameter D_w	9.525 mm
Number of balls z	17
Reference grease quantity G_{ref}	3.3 cm ³
Preload class A G_A	170 N
Static axial stiffness, preload class A	146 N/ μ m
Preload class B G_B	340 N
Static axial stiffness, preload class B	192 N/ μ m
Preload class C G_C	680 N
Static axial stiffness, preload class C	254 N/ μ m
Preload class D G_D	1360 N
Static axial stiffness, preload class D	343 N/ μ m



BEARING CORP. LTD.

class D	
Calculation factor f	1.09
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.05
Calculation factor f_{2D}	1.08
Calculation factor f_{HC}	1.02
Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.2 kg